

Product information

Motorbike Gear Oil 80W-90

PI 10/26/03/2019



Description

High-performance high-pressure gear oil made from carefully selected base oils and multipurpose additives. For universal use in all types of motorbike engine according to API classification GL 4.

Properties

- high wear resistance
- high pressure-absorption capability
- reduces running noise
- excellent high and low temperature behavior
- high resistance to aging
- does not attack common sealing materials



Available pack sizes

1 l Can plastic 3821
D-GB-I-E-P

Specifications and approvals:

API GL4

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

SAE class (gear oils)	80W-90 SAE J306
Density at 15 °C	0,895 g/cm ³ DIN 51757
Viscosity at 40 °C	143 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -26°C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	100 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L3,0 DIN ISO 2049

Areas of application

For motorcycle transmissions and final drives with normal to high loading. Comply with the transmission manufacturer's instructions.

Application

When selecting, keep to the viscosity class stipulated by the transmission manufacturer. Mixable with all branded gear oils. Full effectiveness only when used unmixed.